

Infratekk - Hand Pumps

Infratekk Pumps Series



Pump Stage	Model	Pressure In Bar		Oil Displacement in stoke per (cc)		Oil Tank Cap. in Ltrs	Usable oil volume in Ltrs	Force apply on Handle in kg	Dry Weight in Kg	Pressure Setting Range
Single Speed	IHP 12/2		700		2.8	2	1.4	40	8.0	400b-kg/cm ²
	IHP 16/2		350		5.0	2	1.4	50	8.0	350-kg/cm ²
Double Speed	IHP 3012/5	30	700	17	2.8	2	1.4	40	11.2	400b-700 kg/cm ²
	IHP 3012/5	30	700	17	2.8	3	2.2	40	12.2	400b-700 kg/cm ²
	IHP 5012/5	30	700	49	2.8	5	3.8	40	18.5	400b-700 kg/cm ²
	IHP 5012/5	30	700	49	2.8	6	4	40	19.0	400b-700 kg/cm ²
	IHP 5012/7	30	700	49	2.8	8	7.4	40	20.0	400b-700 kg/cm ²
	IHP 5012/13	30	700	49	2.8	12	8.0	40	21.0	400b-700 kg/cm ²
	IHP 5012/20	30	700	49	2.8	20	16.2	40	28.0	400b-700 kg/cm ²
	IHP 5016/5	30	350	49	5.0	5	3.8	50	18.5	350-kg/cm ²
IHP 5016/13	30	350	49	5.0	12	8.0	50	21.0	350-kg/cm ²	

NOTE:

Single Speed Pumps - generally use 10T to 30T Jacks. These pump flow constantly.

Double Speed Pumps - generally use above 30T Jacks. These pump flow dually.